

NEWLIFE® INTENSITY®

Stationary Oxygen Concentrator

HIGH FLOW AND HIGH PRESSURE COMBINED

Combining high flow and high output pressure makes the Intensity the premier high flow stationary concentrator for at home and facility use.



HIGH-PRESSURE APPLICATIONS

The Intensity has an output pressure of 20 psi (137.9 KPa), more than double any other high flow concentrator.



8 LPM OR 10 LPM OPTIONS

The NewLife® Intensity is available in both 8 LPM and 10 LPM models. The 8 LPM is an ideal low cost option where the highest flow settings are not required. Drawing 30% less power than the 10 LPM models, the 8 LPM still provides the high output pressure for medical applications.



DUAL FLOW OPTION

Unique to the NewLife® series of concentrators, the Dual Flow option features two separate flow meters that can provide a total of 8 or 10 LPM. Allowing two patients to get oxygen from one machine simultaneously, this is perfect for hospitals, long term care facilities, clinics, waiting rooms, or day and night time settings.



CAIRE Contact Information:

Providers Toll Free
1.800.482.2473
Patients Toll Free
1.877.704.0878
www.cairemedical.com

SEE PRODUCT WARRANTY STATEMENT FOR COMPLETE INFORMATION. Please consult the applicable product instructions for use for product indications, contraindications, warnings, precautions, and detailed safety information.
© 2018 CAIRE Inc. All Rights Reserved.

NEWLIFE® INTENSITY®

Stationary Oxygen Concentrator

Includes

- Oxygen Concentrator
- Humidifier Adaptor Tube

Product Features

- High output pressure
- Optional oxygen monitor
- Easy to service and maintain
- Time-proven NewLife® ruggedness and reliability
- Dual flow option available
- Dual function hour meter



Specifications

FLOW RATE

8L: 2-8 LPM
10L: 2-10 LPM

DIMENSIONS

27.5 x 16.5 x 14.5 in (69.9 x 41.9 x 36.8 cm)

WEIGHT

8L: 54 lbs (24.5 kg)
10L: 58 lbs (26.3 kg)

SOUND LEVEL

8L: 52 dB(A)
10L: 55 dB(A)

O₂ CONCENTRATION

8L: @2-7 LPM: 92%+3.5%/-3%;
@8 LPM: 90%+5.5%/-3%
10L: @2-9 LPM: 92%+3.5%/-3%;
@10 LPM: 90%+5.5%/-3%

OPERATING ENVIRONMENT

-4° to 140°F (-20° to 60°C),
15-95% humidity

STORAGE ENVIRONMENT

-4 to 140°F (-20 to 60°C)
15-95% humidity

MAXIMUM TUBING

200 ft (61 m)

MAINTENANCE

SCHEDULE

Felt Filter (230 V only) – 1 Year
Replacement
Intake Filter – Clean Weekly

WARRANTY

3 Years

Available Accessories



HUMIDIFIER ADAPTOR & BOTTLE

Humidifier Adaptor (9 in/23 cm)

Ask your doctor or therapist if
humidification is right for you.



NASAL CANNULAS

Various lengths are available.

(7 ft and 25 ft)

Talk to our Customer Service team
to learn more.



OXYGEN TUBING

Comes in: 7 ft (2.1 m), 25 ft (7.6 m),
and 50 ft (15.2 m).



CAIRE Contact Information:

Providers Toll Free
1.800.482.2473
Patients Toll Free
1.877.704.0878
www.cairemedical.com

SEE PRODUCT WARRANTY STATEMENT FOR COMPLETE INFORMATION. Please consult the applicable product instructions for use for product indications, contraindications, warnings, precautions, and detailed safety information.
© 2018 CAIRE Inc. All Rights Reserved.

ML-CONC0084 C