

Astral[®] series



Astral PS/SVt quick setup guide

Pressure Support with Safety Tidal Volume (PS/SVt) mode is a Volume-Assured Pressure Support (VAPS) mode, which is often used to treat patients with chronic obstructive pulmonary disease (COPD) and neuromuscular disease (NMD). PS/SVt mode offers a volume guarantee with every patient breath. This mode also provides patients with the flexibility to use a traditional vented mask with Standard air tubing (6 ft). PS/SVt is now available on the Astral[™] series leak circuit, which enhances leak compensation with Vsync technology for patients with persistent mask or oral leak. Follow these step-by-step instructions to set up Astral on PS/SVt.

Choose a single limb leak adapter (PN27942) to configure PS/SVt in leak mode:






To access **clinical mode** from the patient home screen, **press and hold the lock** key for 3 seconds:



Next, select "20 minutes" or "Unlimited." The Main Settings screen is now displayed:



To use the **Setup Assistant**, follow all steps according to the LED screen prompts. Select "Adult" as the patient type and "single limb leak circuit" as the circuit type. During this process, ensure masks are not in place.

	r I		Standby	85%
cmH2O 60 -	Programs			ර්ථ
50 -	Setup Assistant			v
40 - 30 -	Circuit Settings	Setup Assistant		Start >
20 - 10 -	Data transfer			4
0-	Device config.			i
Vti mL	MVi L/min	Resp. rate per min St	art vent.	K Spont. I:E

3

From the on-screen selections, press "Ventilation mode", and then select "PS/SVt":



Turn on "Safety Vt (SVt)" if a volume guarantee is prescribed:

	1 ← ^{P1} PS					Standby 55%			*	
cmH:0	Programs	Main settings	Patie							GD
60 - 50 -	Setup Assistant	Ventilation	mode	PS	; >					
40 -	Circuit	PS	7.0	PEEP	5.0	Resp. rate	15			R
30 -	Settings	cmH:O		cmH:O Rise time		per min Ti Min	0.00	Ti Max	1.50	\triangle
20-	Data transfer			msec	200	sec	0.20	sec	1.50	•
0-	Device config.	Safety Vt mL	Off			Trigger Medium	~	Cycle %	25	i
Vte mL	MVe L/min	Resp. per m		\bigcirc	Start v	ent.		- % Spont Trig.	t. Leak L/min	

Set additional settings per your prescription:

4

5

6

-		P1 PS.SV		Standby	85%	*
cmH.O	Programs	Main Pati settings inf				GD
60 - 50 -	Setup Assistant	Ventilation mode	PS >]		-
40-	Circuit	р s 7.0	peep 5.0	Resp. rate 15		ы В
30 -	Settings	cmH2O	cmH:0 Rise time	per min Ti Min	Ti Max	\triangle
20-	Data transfer	Contraction of the second	200	sec	1.50	<u> </u>
0-	Device config.	Safety Vt 100 mL	PS max 33.0 cmHi0	Trigger Medium	cycle %	i
Vte mL	MVe L/min	Resp. rate per min	Start v	vent. Ti sec	- [%] Spont. Trig Leak L/min	

 Apply any additional primary settings prescribed by the physician, such as: Pressure Support (PS): 7–9 cmH₂O Positive End-Expiratory Pressure (PEEP): 5–7 cmH₂O Respiratory Rate (RR): 10–12 bpm Safety Vt: 6–8 mL/kg Pressure Support Maximum (PS Max): 20–25 cmH₂O
 (
 Apply Cancel *

8 Initiate therapy with the appropriate vented mask, such as:



AirFit[™]F20 full face mask

AirFit[™]P10 nasal pillows mask

AirFit[™]N20 nasal mask

Please reference the Astral series clinical guide for complete product information, including indications for use, warnings and cautions.



Distributed by ResMed Corp, 9001 Spectrum Center Boulevard, San Diego, CA 92123 USA +1 858 836 5000 or 1 800 424 0737 (toll free). See ResMed.com for other ResMed locations worldwide. AirFit and Astral are trademarks and/or registered trademarks of the ResMed family of companies. Specifications may change without notice. For patent and other intellectual property information, see ResMed.com/ip. © 2018 ResMed. 278126/1 2018-05

ResMed.com